



SEALING MAT WITH MAGNETIC BACKING

Purpose and Features: The sealing magnetic mat is designed for quick temporary closure of hatches, drains, manhole covers, and similar applications. Its technical specifications include an 8-millimeter material thickness and construction from polyurethane.

Features and Benefits of this product:

- + Protection against hazardous substance leaks: The sealing mat provides rapid temporary sealing of hatches, drains, and similar devices, preventing leaks of hazardous substances.
- + Resistance to chemicals: The material is highly resistant to most chemicals, oils, and aqueous liquids.
- + Reliability and multiple uses: The sealing mat is made from durable polyurethane designed for multiple uses. It can be easily cleaned with soap and water, making it an economical and practical solution.



Note: Sealing mats are not intended for walking on and do not conduct electricity.

Individual Characteristics: In addition to standard diameters of Ø 450 mm and Ø 850 mm, it is possible to order this product with individual characteristics tailored to the customer's needs.

Application: The sealing magnetic mat is recommended for use in the following situations:

- + For temporary sealing in emergency situations.
- + For preventive purposes, preventing potential leaks.
- + As protection against leaks of hazardous substances.

Flexible and airtight, this material provides optimal adhesion to surfaces and is equipped with a magnetic strip underneath for secure attachment to hatches and metallic surfaces.

TECHNICAL SPECIFICATIONS

Material thickness	8 mm
Material	Polyurethane
Version	Universal
Application	Leak response (emergency), leak prevention
Feature	Guiding / restraining / capturing
Leak Type	Spray, surface leakage, non-sealing
Frequency of Use	Multiple
Application Area	Interior and exterior
Product Type	Flexible sealants

