



MAGNETIC SEALING MAT

The magnetic sealing mat is designed for the quick, temporary closure of hatches, drains, manhole covers, and similar applications.

It is made from 8-millimeter thick polyurethane for durability and reliability.

- + The sealing mat provides rapid temporary sealing of hatches, drains, and similar devices, preventing leaks of hazardous substances.
- + The material is highly resistant to most chemicals, oils, and aqueous liquids.
- + The sealing mat is made from durable polyurethane designed for multiple uses. It can be easily cleaned with soap and water, making it an economical and practical solution.



Note: Sealing mats are not intended for walking on and do not conduct electricity.

In addition to standard diameters of Ø 450 mm and Ø 850 mm, it is possible to order this product with individual characteristics tailored to the customer's needs.

The Sealing Magnetic Mat is recommended for use in the following situations:

- + For temporary sealing in emergency situations.
- + For preventive purposes, preventing potential leaks.
- + As protection against leaks of hazardous substances.

Flexible and airtight, this material provides optimal adhesion to surfaces and is equipped with a magnetic strip underneath for secure attachment to hatches and metallic surfaces.

TECHNICAL SPECIFICATIONS

Material thickness	8 mm
Material	Polyurethane
Version	Universal
Application	Leak response (emergency), leak prevention
Feature	Guiding / restraining / capturing
Leak Type	Spray, surface leakage, non-sealing
Frequency of Use	Multiple
Application Area	Interior and exterior
Product Type	Flexible sealants



E-mail: econadin@ukr.net
contact@econadin.com
Skype: econad.sie
Web: www.econadin.com, www.econad.com.ua

