



## OIL CONTAINMENT BOOMS

Oil spill containment booms are an economical and versatile tool for containing oil spills and other pollutants floating on the surface of the water.



### **ECONAD FLOATING CONTAINMENT BOOMS ARE USED FOR:**

- Limiting the spread of pollution on the water surface
- Containment, movement, and recovery of oil in the event of oil spills
- Fencing off oil tankers during cargo operations, providing reliable protection of water areas from pollution
- Containing oil spills
- Protecting coastlines, harbors, rivers, and natural reserves from spilled oil
- Isolating areas contaminated with oil products during cleanup operations





**ECONAD**

# OIL CONTAINMENT BOOMS



Product type	500	750	900	1000	1200
Freeboard (mm)	200	260	320	360	380
Skirt (mm)	300	390	460	560	605
Force tension (mm)	8	15	25	40	50
Application Limits					
Section length (m)	10/15/20	20	20	20	20
Wind speed, (m/s)	8	15	18	20	20
Section weight, (kg)	45	75	130	195	260
Trawling speed, (kt)	1	2	2	2.5	3



E-mail: [econadin@ukr.net](mailto:econadin@ukr.net)  
 contact@econadin.com  
 Skype: econad.sie  
 Web: [www.econadin.com](http://www.econadin.com), [www.econad.com.ua](http://www.econad.com.ua)

